



### FEATURES

- ◆ Intuitive handling
- ◆ Precise mechanics
- ◆ High brightness and brilliant image quality
- ◆ Convex and concave curveable
- ◆ Edge protection

The INFiLED DB3.4 LE does not only convince with its modern design, but also offers outstanding image quality with a pixel pitch of 3.47 mm. Even with wide viewing angles, it retains its uniformity and high contrast level. The embedded edge protection as well as the intuitive mechanics of INFiLED DB3.4 LE allow an easy 1-man installation. Besides the product can also be curved concave as well as convex according to appropriate latches.

Do you want to learn more?

[www.lang-ag.com](http://www.lang-ag.com)

# INFILED DB3.4 LE



## TECHNICAL SPECIFICATIONS

<b>Model designation</b>	DB3.4 LE
<b>Pixel pitch</b>	3.47 mm
<b>Brightness</b>	2200 nit
<b>Pixel density</b>	144 x 144 px/cabinet; 82,944 px/m <sup>2</sup>
<b>LED-type</b>	Black Face and Black Body SMD
<b>Lifespan LED</b>	100,000 hours
<b>Viewing angle</b>	160° horizontal; 160° vertical
<b>Processing</b>	Novastar
<b>Power consumption</b>	Maximum: 200 W/cabinet; 800 W/m <sup>2</sup> Average: 66.7 W/cabinet; 266.7 W/m <sup>2</sup>
<b>Input voltage</b>	110 - 240 V / 50 - 60 Hz
<b>Operating temperature</b>	-10 to +45 °C
<b>Cabinet dimensions</b>	500 x 500 x 76 mm (W x H x D); (=0.25 m <sup>2</sup> )
<b>Weight</b>	9.35 kg/cabinet; 37.4 kg/m <sup>2</sup>
<b>Max. height (hanging/stacking)</b>	18 cabinets / 12 cabinets
<b>Accessibility</b>	Front / rear service
<b>Curving</b>	Concave and convex
<b>Protection rating</b>	IP30
<b>Certifications</b>	CE, RoHS, EMC class A, ETL, FCC, LVD

Do you want to learn more?

[www.lang-ag.com](http://www.lang-ag.com)