



*GhosT-OLED Full Kit  
- front view -*

## GhosT-OLED

- ▶ transparent OLED with vivid colors and high transparency
- ▶ various mechanical options for different applications
- ▶ easy transformation of full kit from table to straight mode
- ▶ touch version available
- ▶ three years warranty

### EXACT solutions GhosT-OLED meets LG

EXACT solutions GhosT-OLED is powered by the latest LG T-OLED 55EW5F-A display. The innovative transparent OLED technology results in vivid colours, a wide viewing angle and of course the futuristic and eye catching transparency. The GhosT-OLED range is especially developed for the requirements and the usage on the pro AV market. Due to various product versions and a fully redesigned concept, the GhosT-OLED can easily be installed into walls or tables, used as a stand-alone solution or to create a transparent video wall and can even be made touchable. For any kind of installation there is always the right version or accessory available and if not, EXACT solutions will offer help finding the right customised solution. All GhosT-OLED products powered by LG come with a three year warranty.

### MODEL DESIGNATION

GHOST55-HK:	GhosT-OLED Half Kit open frame version for easy integration
GHOST55-FK:	GhosT-OLED Full Kit for rental and stand-alone applications
GHOST55-TK:	GhosT-OLED Touch Kit, IR overlay frame for GhosT-OLED



*GhosT-OLED Half Kit  
- back view -*



*GhosT-OLED Full Kit  
- back view -*



*GhosT-OLED Full Kit equipped with Touch Kit  
- front view -*

### TECHNICAL SPECIFICATIONS

#### Panel

Screen size:	55"
Panel technology:	OLED
Aspect ratio:	16 : 9
Native resolution:	1,920 x 1,080 pixels (FHD)
Brightness (typ.):	400 nit / 150 nit (average picture level 25 % / 100 %)
Transparency (typ.):	38 %
Viewing angle:	178° x 178° (H x V)
Response time:	1 ms (G to G), 8 ms (MPRT)
Surface treatment (haze):	hard coating (2H), anti-reflection treatment of the front polarizer (reflectance typ. 14 %)
Lifetime (typ.):	30,000 hours; operation hours: 18 hours/7 days*1
Orientation:	landscape & portrait

#### Touch overlay

Technology:	IR diodes
Ambient light proof:	yes
Simultaneous touch points:	12
Operating system:	Windows 10/8/7/Vista/XP, Mac OS X, Ubuntu/Fedora
Programming interface:	Windows Native Touch / TUIO
Connection:	USB A

#### Connectivity

Input:	HDMI, DP, USB (2)
Output:	DP, audio
External control:	RS232C in/out, RJ45 (LAN) in/out, IR in

#### Power

Power supply:	100 - 240V~, 50/60Hz
Power type:	built-in power
Power consumption:	typ. 309 W*2, max. 318 W*2

#### Environment conditions

Operation temperature:	5 °C to 35 °C
Operation humidity:	10 % to 80 %

Warranty	3 years
----------	---------

\*1 moving video only

\*2 8 color bar