

Compact Remote Camera Controller

AW-RP60

Remote Camera Controller



KEY FEATURES

- Equipped with a 3.5-type LCD screen
- Flexible customisation features
- New Joystick with enhanced operability
- PoE+ support/Advanced camera adjustment
- Control of up to 200 remote network cameras

Introducing the all-new AW-RP60 Remote Camera Controller. Equipped with a large LCD to display a GUI menu screen with clear visibility and an improved joystick for smoother control, this controller is compatible with all current Panasonic PTZ models. Thanks to the improved GUI, now all important information about the cameras, such as iris, zoom and focus can be seen at all times directly on the screen. The AW-RP60 is also capable of supporting up to 200 cameras in 20 groups, manages 100 presets and comes with PoE support allowing for an easy integration.

SPECIFICATIONS

Current Consumption	0.9 A (XLR connector input), 0.3 A (PoE power supply)
Power Requirements	12 V DC (10.8 V to 13.2 V)
Mass	1.5 kg (3.31 lbs)
Dimensions (W x H x D) (mm)	W 210 mm x H 92 mm x D 177 mm (excluding protrusions)
Dimensions (W x H x D) (inch)	8-9/32 inches x 3-5/8 inches x 6-31/32 inches (excluding protrusions)
Display	3.5-type liquid crystal (QHD 960 x 540)
Connection Specifications	<p>No. of Connectable Cameras : 200 (IP), 5 (RS422) *Up to 100 for cameras other than the AW-UE150</p> <p>Remote Camera Selection : 5 (6 to 200 controlled from the LCD)</p> <p>No. of Camera Groups : 20 (10 units/group)</p> <p>No. of Memory Presets : 100</p>
PoE*	IEEE802.3af standard: 42 V to 57 V DC (Camera Input)
Note	*PoE is the abbreviation for Power over Ethernet.

URL: <https://business.panasonic.co.uk/professional-camera/Compact-Remote-Camera-Controller/aw-rp60>

CONTACT

Web: <https://business.panasonic.co.uk/professional-camera/contact-us>