

# RC400T event controller

Ref. RC400T



New event controller for the LivePremier™ multi-screen live presentation systems



## Presentation

The RC400T event controller has been designed to greatly increase the level of operational efficiency and to give instant access to the crucial functionalities of the LivePremier™ image processor such as screens, layers, sources and presets. The RC400T comes with a small footprint design and rugged housing, and offers 56 user programmable buttons, a high-resolution T-bar and a three-axis joystick for easy and fast PIP sizing and programming. This makes it the perfect solution for most control environments from large-scale live events (music shows, new product launches, industry conferences...) to multi-purpose event auditoriums.

## Key Features

- Heavy-duty, compact design
- Designed for fault-free operation
- Instant access to crucial functionalities
- 48 user-programmable buttons with customizable LCD displays
- 8 user-assignable custom functions buttons
- High-resolution T-bar
- Three-axis joystick for easy and fast PIP sizing and programming
- Can be deployed both on a desk or recessed in the console surface

## Technical Specifications

- Dimensions**
  - ▶ W 22.44" x H 4.82" x D 15.04"
  - ▶ L 570 mm x H 122.5 mm x P 382 mm
- Weight without accessories**
  - ▶ 8 kg / 17.63 lbs
- Operating conditions**
  - ▶ Temperature: 0 to 40°C (32 to 104°F)
  - ▶ Humidity: 10% to 80%, non-condensing
- Noise (@1,6m height @25°C)**
  - ▶ Front: 35 DBa@1m
  - ▶ Rear: 35 DBa@1m
- Thermal dissipation**
  - ▶ 85 BTU/hr
- Warranty**
  - ▶ 3-year warranty on parts and labor back to factory
- Power supply**
  - ▶ 100-240 VAC 50/60Hz 2.2A
  - ▶ Fuse cartridge T2,5A 250VAC 5x20mm
  - ▶ Max consumption: 25 W
- Safety Compliance**
  - ▶ IEC/UL/EN 62368-1
  - ▶ CSA22.2#62368-1
  - ▶ (UL Listed E359143)
- EMC & Environmental Compliance**
  - ▶ EN55032, EBS5024, EN61000, FCC part15, ICES
- Supplied with**
  - ▶ 1 x Power supply cord
  - ▶ 1 x Quick start guide including safety instructions

Specifications subject to change without prior notice

RC400T\_EN-02/07/2020