


SMPTE 311M-HD-Hybrid-Camera Cable

Hybrid-HDTV-Camera Cable



Application

This Hybrid HD Camera Cable 2SM 9/125 + 4 x AWG20 + 2 x AWG24 acc. to SMPTE 311M-Standard contains Single-Mode Optical Fibres, Auxiliary- and Signal Conductors. It is used in professional video productions for simultaneous transmission of energy, video, audio and control signals and is intended to interconnect Camera Units and Base Stations in conjunction with the Connector Interface Standard. It is suitable for all new digital camera systems of well-known manufacturers.

Standards

SMPTE 311M

Flame resistance

PUR/PUR rubber designed for mobile use, not fixed installation in construction works

FRNC jacket: IEC 60332-1, IEC 60754-2, IEC 61034, Class E_{ca}

FRNC-C jacket: IEC 60332-3-24

Construction

Element 1: Auxiliary Conductors AWG20 (4 x 0.6 mm²)

Conductor	tinned stranded copper wires, 19 x 0.20 mm, diameter 1.0 mm
Insulation	HDPE, diameter 1.5 mm
Identification	2 x black, 2 x white

Element 2: Signal Conductors AWG24 (2 x 0.22 mm²)

Conductor	tinned stranded copper wires, 7 x 0.20 mm, diameter 0.6 mm
Insulation	HDPE, diameter 1.1 mm
Identification	1 x red, 1 x grey

Element 3: Fibre Optic Single Mode (2 x 9/125µ) (FRNC-C with Breakout fibers)

Mode field diameter	at 1310 nm, diameter 9.5 µm ± 1 µm
Cladding diameter	diameter 125 µm ± 1 µm
Concentricity error	≤ 1 µm
Coating material	UV-cross-linked Acrylate, diameter 245 µm
Buffer material	Thermoplastic, diameter 0.9 mm
Identification	1 x blue, 1x yellow

Element 4: Strength Member AWG16 (1 x 1.22 mm²)

Conductor	galvanized steel wires, diameter 1.6 mm
Insulation	HDPE, diameter 2.1 mm
Identification	1 x white

SMPTE 311M-HD-Hybrid-Camera Cable

Construction

Stranding	Core: 1x Element 4, diameter 2.1 mm Layer: 4x Element 1 + 2x Element 2 + 2x Element 3 in the outer interstices 4x fibrillated Polypropylene as needed for roundness, diameter 5.2 mm Sequence according to the above drawing
Wrapping	1 x non-woven fabric tape, diameter 5.4 mm
Screen	Copper wire braid, tinned 95% opt. coverage, diameter 5.9 mm
Sheath	PUR or FRNC or FRNC-C (FRNC-C with additional Al-Pet foil) diameter 9.2 mm black, RAL 9005
Printing	PUR: DRAKA SMPTE 311 M Zero-Loss HD Cable + batch number + meter marking FRNC: DRAKA SMPTE 311 M Zero-Loss HD Cable FRNC + batch number + meter marking FRNC-C: DRAKA SMPTE 311 M Zero-Loss HD Cable FRNC-C + batch number + meter marking Armoured: DRAKA SMPTE 311 M Zero-Loss HD Cable FRNC-C armoured + batch number + meter marking

Mechanical properties

Temperature range PUR (FRNC)	during operation	- 40° C to + 70° C (-25°C to +60°C)
Temperature range FRNC-C	during operation	-20°C to + 70° C
Max. humidity		95 %

Electrical properties

at 20°C

Auxiliary Conductors AWG20 (4 x 0.6 mm²)

DC resistance		≤ 35.3 Ω/km
Loop resistance		≤ 70.6 Ω/km
Insulation resistance		≥ 10 ⁴ MΩ*km
Test voltage		1750 V _{AC rms}
Operating voltage		≤ 300 V _{AC rms}

Signal Conductors AWG24 (2 x 0.22 mm²)

DC resistance		≤ 97.5 Ω/km
Loop resistance		≤ 184 Ω/km
Insulation resistance		≥ 10 ⁴ MΩ*km
Test voltage		1750 V _{AC rms}
Operating voltage		≤ 300 V _{AC rms}

Overall screen

DC resistance		≤ 20 Ω/km
---------------	--	-----------

Optical properties

at 20°C

Fibre Optic Single Mode (2 x 9/125µ)

Cut-off wavelength		1100 – 1350 nm
Attenuation	at 1310 nm	0.5 dB
Dispersion	at 1310 nm	3.5 ps/nm*km

SMPTE 311M-HD-Hybrid-Camera Cable

Technical data

Product code	Type	Weight kg/km	Standard delivery length m	Drum size PWD	Copper content	Tensile force N	Minimum bending radius mm	Storage
60014967	9.2mm SMPTE 311M Hybrid Camera Cable PUR	115	1000	760/470/500	47.2	800	65	inside
60011474	9.2mm SMPTE 311M Hybrid Camera Cable PUR rubber	115	1000	760/470/500	47.2	800	65	inside
60043344	9.2mm SMPTE 311M Hybrid Camera Cable FRNC IEC 60332-1	115	1000	760/470/500	47.2	800	90	inside
60049477	9.2mm SMPTE 311M Hybrid Camera Cable FRNC-C IEC 60332-3-24	138	1000	760/470/500	47.2	800	90	inside
60056019	15mm SMPTE 311M Hybrid PUR Camera Cable	250	1000	EW90	47.2	800	150	inside
60028797	16mm SMPTE 311M Hybrid PUR Camera cable	250	1000	EW90	47.2	800	160	inside
93012600	Armoured SMPTE 311M Hybrid Camera Cable FRNC-C	300	1000	EW90	47.2	800	120	inside

© PRYSMIAN GROUP 2016, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.