


TD | TOUCH DRIVE



Specifications

Switcher resources, video specifications, power rating, and port pinouts.

Ports



USB Port

Note: The panel software can only mount a single USB drive at a time. The remaining ports can be used for an external mouse and keyboard.

- **File System:** FAT32
- **USB 2.0:** Type-A located on the back of the panel.
- **USB 3.0:** Type-A located on the side of the backplash on some panels.

Hardware Weights

Hardware	Weight
TD1C Panel	10 lbs (4.54 kg)
TD1 Panel	14 lbs (6.35 kg)
TD2 Panel	21 lbs (9.53 kg)
TD2S Panel	27 lbs (12.25 kg)
TD3S Panel	
CB1 Panel	13 lbs (5.90 kg)
CB1S Panel	17 lbs (7.71 kg)
CB2 Panel	20 lbs (9.07 kg)
CB2S Panel	26 lbs (11.79 kg)
CB3S Panel	35 lbs (15.88 kg)
CB3X Panel	40 lbs (18.14 kg)
CB9 Panel	8 lbs (3.63 kg)

Environmental Characteristics

All Switchers	
Ambient Temperature Range	Operating: 0 - 40°C (32 - 104°F) Storage: -20 - 85°C (-4 - 185°F)

Network Ports

The following network ports are used:

- DashBoard (OGP) — 5253
- DashBoard (JSON) — 5254
- DashBoard Main — 5253
- DashBoard Sat 1 — 5255
- DashBoard Sat 2 — 5256
- DashBoard SoftPanel — 5257
- FTP — 21
- NTP — 123
- Panel (port on panel) — 3333
- RossTalk — 7788
- SLP — 427
- SSH — 22
- TFTP — 69
- TSL — 5727
- Web Server 1 — 80
- Ulritouch — 5254
- SideShot-NG — 5255

Power Consumption — Panel

	TD1C	TD1	TD2	TD2S	TD3S
Power	50W 3.33A 15V	73W 4.87A 15V	85W 5.67A 15V	107W 7.13A 15V	165W 11A 15V
Input Voltage	100 - 120V~, 220 - 240V~, 47-63Hz				

Table 1: Carbonite Black Control Panels

	CB9	CB1	CB1S	CB2	CB2S	CB3S	CB3X
Power	24W 2A 12V	25W 2.1A 12V	30W 2.5A 12V	35W 2.9A 12V	45W 3.8A 12V	65W 5.4A 12V	80W 6.7A 12V
Input Voltage	100 - 120V~, 220 - 240V~, 47-63Hz						