



| | |
|--------------------------------|---|
| Model designation | LUNA |
| Pixel pitch | 1,93 mm |
| Brightness (max.) | 1,000 nit |
| Application area | 256 x 256 px/Cabinet; 268,324 px/m ² |
| LED-type | SMD, CCT (Common Cathode Technology), GOB (Glue on Board) |
| Scan Ratio | 1/16 |
| Grayscale | 16 bit |
| Lifespan LED | 100,000 hours |
| Viewing angle | 160° horizontal, 160° vertical |
| Processing | Novastar |
| Power consumption | Maximum: 137 W/Cabinet; 557 W/m ² Average: 46 W/Cabinet; 187 W/m ² |
| Input voltage | 100 - 240 V / 50 - 60 Hz |
| Ambient temperature | 0 to 45 C° |
| Operating humidity | 10 to 90% |
| Cabinet dimensions | 496 x 496 x 55 mm (WxHxD) |
| Weight | 9,2 kg |
| Maintenance | Front Back Service |
| Curving | concave(-): 2,5, 5,0, 7,5, 10,0 |
| Cabinet connection | Compatible to exhibition stand systems |
| Protection (Front/Back) | IP43 Front / IP 20 Back |
| Certification | CE, EMC, EMC class B, ETL |