



<b>Model designation</b>	INFILED AR 10.41
<b>Pixel pitch</b>	10.41 mm
<b>Brightness (max.)</b>	5,000 nit
<b>Application area</b>	Outdoor
<b>Pixel density</b>	48 x 96 px/cabinet; 9,216 px/m <sup>2</sup>
<b>LED-type</b>	White Face and Black Body Gold Wire SMD
<b>Lifespan LED</b>	100,000 hours
<b>Viewing angle</b>	160° horizontal; 110° vertical
<b>Processing</b>	Novastar
<b>Power consumption</b>	Maximum: 368 W/cabinet; 736 W/m <sup>2</sup> Average: 123 W/cabinet; 246 W/m <sup>2</sup>
<b>Input voltage</b>	100 - 240 V / 50 - 60 Hz
<b>Ambient temperature</b>	-20 to +45 °C
<b>Operating humidity</b>	10 to 90 %
<b>Cabinet dimensions</b>	500 x 1,000 x 70 mm (W x H x D); (= 0.5 m <sup>2</sup> )
<b>Max. Overall height (hanging/standing)</b>	15 Cabinets / 6 Cabinets
<b>Weight</b>	12.4 kg/cabinet; 24.8 kg/m <sup>2</sup>
<b>Maintenance</b>	Front/Back maintenance
<b>Protection (Front/Back)</b>	IP65
<b>Certification</b>	CE, RoHS, EMC class B, TÜV