



<b>Model name</b>	LEDGEN D
<b>Pixel pitch</b>	0.9375 mm
<b>Brightness (max.)</b>	≥ 1,200 nit
<b>Pixel density</b>	640 x 360 px/cabinet; 1,137,778 px/m <sup>2</sup>
<b>LED-type</b>	COB (Chip-on-Board), Flip Chip
<b>Lifespan LED</b>	100,000 hours
<b>Viewing angle</b>	160° horizontal; 160° vertical
<b>Processing</b>	Novastar
<b>Bit depth</b>	16 bit
<b>Refreshrate</b>	7,680 Hz
<b>Power consumption</b>	Maximum: 350 W/m <sup>2</sup> Average: 120 W/m <sup>2</sup>
<b>Input voltage</b>	100 - 240 V
<b>Operating Temperature</b>	-10 to 40 °C
<b>Operating humidity</b>	10 to 90 %
<b>Cabinet dimensions</b>	600 x 337 x 39 mm (WxHxD); (= 0.20 m <sup>2</sup> )
<b>Weight</b>	6 kg/cabinet
<b>Protection (Front/Back)</b>	IP20
<b>Certifications</b>	CE, RoHs, EMC class B, TÜV, DIN VDE, CCC, FCC, Intertek ETL